

1.60 (MR8) Spherical Single Vision Blank 65 / 70 mm

ASAHI-LITE®

Diameter (mm)	Nominal convex curve (D)	Actual convex curve (N=1.530) (D)	Radius of curvature R1 (mm)	Sagitta depth gauge 50 mm bell (mm)	Center thickness (mm)	Edge thickness (mm)
70 SFX	Plano	0,00	26.500,00	0,01	9,5	17,0
70	Plano	0,00	26.500,00	0,01	7,0	15,0
70	0.50	0,53	1.000,00	0,31	7,6	15,0
70	1.50	1,55	341,94	0,92	9,0	15,0
70	2.00	2,16	245,37	1,28	9,5	15,0
70	3.00	2,99	177,26	1,77	8,5	13,0
70	4.00	3,68	144,02	2,19	9,5	13,0
70	5.00	4,76	111,34	2,84	10,5	13,0
70	6.00	5,88	90,14	3,54	7,0	7,0
70	7.00	6,87	77,15	4,16	8,2	7,0
70	8.00	7,95	66,67	4,87	10,0	7,0
70	9.00	8,93	59,35	5,52	11,5	7,0
70	10.00	10,05	52,74	6,30	13,0	7,0
65	10.00	10,05	52,74	6,30	13,0	8,0
65	11.00	11,20	47,32	7,14	13,0	6,5
65	12.00	12,35	42,91	8,03	15,4	7,0
65	14.00	14,16	37,43	9,57	18,3	7,0